Uniden[®]

UHF CB MOBILE 80 Channel* | 5W UH5060



Mount Anywhere



Mini Compact Size



Dual Speakers



Remote Speaker Mic

UH5060 CB MOBILE



AT850BK ANTENNA



MGU-01 "ZYTYPE MOUNT



Uniden Selebrating YEARS OF GLOBAL EXCELLENCE

5 Year Warranty^a

BUILT RUGGED

Uniden[®]

UHF CB MOBILE 80 Channel* 5W

UH5060 + ANT + BRACKET



INCLUDED IN THE BOX

- 1 x UH5060 Radio
- 1 x Remote Speaker MIC
- 1 x Microphone Hanger
- 1 x Extension Cable
- 1 x Mounting Bracket
- 1 x Owner's Manual

ANTENNA

1 x AT850BK Antenna

ANTENNA MOUNTING BRACKET

1 x MGU-01



UH5060

80 UHF Narrowband Channels*:

Choose from up to 80 frequencies to transmit and receive messages.

Mini Compact Size:

24mm (H) x 100mm (W) x 95mm (D).

Remote Speaker Microphone with built-in Large LCD Display: Control

all functions and features remotely. including volume and power on/off

LCD Backlight, Brightness and **Contrast Controls**

5W Transmission Power: Maximum

Dual Speaker with Synchronised Volume: Speaker at the Base and Microphone

Extension Cable: Use the cable extension and keep the radio hidden from view

Signal Strength and RF Power (S/RF) Meter

Instant Channel Programming and Recall: Program any channel as the Instant priority channel and recall it at the touch of a button located on the mic.

Open Scan: This scan mode scans all channels in memory and locks on any active channel.

Group Scan: This scan mode allows the user to select the channels they wish to monitor/listen to in a group, along with a priority channel (priority

Dual Watch: Allows you to monitor the priority channel for activity every two seconds while monitoring another UHF channel at the same time.

Monitor On/Off Function

Duplex Capability: Allows the radio to operate via a local repeater station, if available, which re-transmits your signal over a wider area. Up to an extra 30-100km depending on location, height and availability of local repeater

Key Beep On/Off Function

Busy Channel Lock-out Function: Disables your transmitter while activity

Roger Beep Function On/Off: Confirmation tone indicates the completion of your transmission.

is detected on the channel.

Call Tone Function: Choose from one of 5 wake-up tones to initiate your transmission with the touch of one microphone button.

Auto Squelch: Adjustable 3 Level Auto Squelch function.

Volume Control: Adjustable volume control levels (0 - 7)

External Speaker Jack

CTCSS (Continuous Tone Coded Squelch system) and DCS (Digital

Coded Squelch) Codes: Choose from 38 (CTCSS) and 104 (DCS) digital codes that can be sent with your transmission. The code is recognized by the selected receivers enabling them to receive the transmission. Receivers that do not recognize the code remain silent therefore blocking out unwanted conversations.

Designed & Engineered in Japan

Built Rugged for Australian and New Zealand Conditions

AT850BK **KEY FEATURES**

- Elevated Feed and Fibreglass Whip with Black Heat Shrink 6.6 dBi Gain
- Highly Flexible Whip
- Parallel Style Stainless Steel Spring
- Ground Independent
- 4.5m Low Loss Coax Cable
- Terminated FMF Female
- Connector and PL259 Adaptor

MGU-01 KEY FEATURES

- Cable Slot
- Polished Stainless Steel
- Thickness 2 0mm

* Please note CH 22 & 23 are used for telemetry and telecommand applications, voice communications are not permitted on these channels and transmission is inhibited. CH 61, 62 & 63 are for future use and are receive only channels.

One vear warranty on any included accessories Specifications subject to change without notice. For full range & details call 1300 366 895, scan QR code or visit uniden.com.au









