



Uniden Australia Pty Ltd

73 Alfred Road
Chipping Norton 2170 NSW
Tel: 02 9599 3355 | Fax: 02 9599 4018
www.uniden.com.au



UBCT-8

250 Channel TrunkTracker III Mobile Scanner

PRINT this page

EMAIL a friend

Range Brochure PDF

Operating Manual PDF

This Desktop scanner with Trucktracker III Trunking Radio Trace Technology offers 250 programmable memory channels - 12 bands. Offering the new Ground Breaking Technology Close Call RF Capture Technology this scanner automatically Listens for any nearby or close transmissions and once they occur the scanner immediately tunes in to this frequency which is ideal for use at events or locations when the transmission is unknown.

Frequency ranges received are 25-512, 806-956 and 1240-1300MHz. Chain searching allows seven different personal search bands and the ability to search up to all five chain locations at once. Priority scanning allows a designated priority channel to be monitored every two seconds.

The UBCT-8 also has Pre-Programmed service search which automatically detects analogue Police channels, Railroad, Air, Marine, UHF CB and AM CB. Also includes 1x Telescopic Antenna, 1x Window Mount Antenna, 1x AC Adaptor, 1x DC Power Cord, 1x Mounting Bracket and 1x Cigarette Lighter Cord.

Suggested Retail: \$429



TRUNKTRACKER III
TRACK AND SCAN WITH EASE

CLOSE CALL™
RF CAPTURE TECHNOLOGY

[TOP](#)

Key Features

Designed and Engineered in Japan

Mobile / Din Size

250 Analogue Channels

12 Bands

Frequency Range: 25-512MHz, 806-956MHz, 1240-1300MHz

Trunktracker III - (Motorola® Analog Trunking, EDACS® / EDACS® SCAT, LTR®)

Close Call RF Capture Technology

Frequency Searching:

- Band Search
- Turbo Search
- Lockout Search
- Analogue Pre Programmed Service Search*:

- > Analogue Police channels
- > Railroad
- > Air
- > Marine
- > UHF CB
- > AM CB

- Frequency Skip

Channel Scanning:

- Memory Channel Scan
 - > Direct Channel Access
 - > Channel Lockout
 - > Priority Scan

:: Uniden Australia ::

- State Scanning

Clone

Control Channel Only Mode

Memory Lock

PC Control

Backlit LCD Display and Keypad

Memory Back Up

Size of Unit (mm): 176.5(W) x 152.0(D) x 50.8(H)

Additional Features:

External Jacks ANT: BNC Type

Internal Speaker: 8ohm.1W

Max Search Speed: 150 Steps/sec

Operating Temperature: -20A - +60Ac

Size of Unit (mm): 176.5(W) x 152.0(D) x 50.8(H)

Weight without battery: 1.1kg

*Please note not all pre-programmed service searches may operate in New Zealand.

[TOP](#) 